

Application No.: 10/560,523Docket No.: 4976-008**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently amended) Device for processing an echo between at least two local communication devices close to one another and coupled to each other by a communication network, to attenuate, in a signal picked up by [[a]]at least one microphone of one of said at least two local communication devices~~device having at least one microphone~~, the components of a signal broadcasted by at least one loudspeaker [[on]]of at least one other of said at least two local communication devices~~devices~~.

the echo processing device comprising:

a receiver for receiving, via a dedicated coupling with at least one other of said at least two local communication devices~~device~~, information representing at least one signal broadcast by at least one loudspeaker ~~on another of at least one other of said at least two local communication devices~~devices,

a signal processing arrangement for modifying the signal picked up by at least one loudspeaker of at least one other of said at least two local~~[[the]] communication device devices~~ from said information representing the broadcasted signal and for weighting the broadcasted signal by a coefficient representing coupling between [[a]]at least one loudspeaker of the at least one other communication device from [[the]]at least one microphone of the communication device.

2. (Previously presented) Echo processing device according to claim 1, wherein the

Application No.: 10/560,523Docket No.: 4976-008

communication device includes the echo processing device.

3. (Previously presented) Echo processing device according to claim 2, further including a controller for controlling echo between at least one of the loudspeakers and at least one microphone of the communication device.
4. (Previously presented) Echo processing device according to claim 1 wherein the information received representing at least one broadcasted signal from at least one other communication device was previously weighted by a coefficient representing the coupling between a loudspeaker of the said at least one other communication device and the microphone of the communication device.
5. (Previously presented) Echo processing device according to claim 4, wherein the signal processing arrangement for modifying the picked up signal is arranged to modify the picked up signal according to the weighted broadcasted signal of at least one other communication device in the reference echo control signal of the communication device.
6. (Currently amended) Device for processing an echo between at least two local communication devices close to one another and coupled to each other by a telecommunication network to attenuate, in a signal picked up by at least one microphone of another of said at least two local communication devices ~~device having at least one microphone~~, the components of a signal broadcasted by at least one loudspeaker of at least one communication device ~~including at least one loudspeaker of at least one communication device~~,

the echo processing device comprising:

a receiver for obtaining information representing the signal broadcasted by the at least one loudspeaker of the communication device,

Application No.: 10/560,523Docket No.: 4976-008

a signal processing arrangement for transferring the information obtained via a dedicated coupling with at least one of the other local communication devices.

7. (Previously presented) Echo processing device according to claim 6, wherein the echo processing device also comprises circuitry for obtaining information representing the coupling between at least one loudspeaker of the said at least one communication device and the microphone of the other communication device.
8. (Previously presented) Echo processing device according to claim 7, wherein the signal processing arrangement is arranged for weighting the information representing the broadcasted signal of the communication device by coefficients associated with information representing the couplings between at least one loudspeaker of the said at least one communication device and the microphone of the other communication device.
9. (Previously presented) Echo processing device according to claim 8, wherein the communication device comprises a plurality of loudspeakers coupled with the at least one communication device so that (a) the signals reproduced by each loudspeaker of the at least one communication device are weighted by respective coefficients representing the couplings between each loudspeaker of the communication device and the microphone of the other communication device and (b) the weighted signals are added.
10. (Previously presented) Echo processing device according to claim 6, wherein the circuitry is arranged for establishing the number of other communication devices and for establishing the number of loudspeakers of the other communication devices.
11. (Previously presented) Echo processing device according to claim 10, wherein the echo processing device also comprises:

Application No.: 10/560,523Docket No.: 4976-008

a generator for generating at least one predetermined audible signal,

a receiver for receiving, by means of coupling with at least one other device, information representing the reception of the audible signal by at least one other device,

the signal processing arrangement being arranged for determining the coupling between a loudspeaker of the said communication device and the microphone of at least one other communication device.

12. (Currently amended) Method of processing an echo between at least two communication devices close to one another and coupled to each other by a telecommunication network to attenuate, in a signal picked up by [[a]]at least one microphone of one of said at least two local communication device-devices having at least one microphone of one of said at least two local communication devices, the components of a signal broadcast by at least one loudspeaker of another-at least one other of said at least two local communication device-devices, the echo processing method comprising the steps of:

receiving, via a dedicated coupling, from at least one other device of said at least two local communication devices, information representing at least one signal broadcast by at least one loudspeaker of at least one other of said at least two communication device-devices,

modifying the signal picked up by [[the]]at least one loudspeaker of at least one other of said at least two local communication device-devices from said information representing the broadcasted signal by weighting the broadcast signal by a coefficient representing [[the]]coupling between [[a]]at least one loudspeaker of the said at least one other communication device and [[the]]at least one microphone of the communication device.

Application No.: 10/560,523Docket No.: 4976-008

13. (Previously presented) Echo processing method according to claim 12, wherein the received information representing at least one broadcast signal of at least one other communication device is weighted by a coefficient representing the coupling between a loudspeaker of the at least one other communication device and the microphone of the communication device.

14. (Previously presented) Echo processing method according to claim 13, wherein the picked up weighted signal is taken into account in a reference echo control signal of the communication device.

15. (Currently amended) Method of processing an echo between at least two local communication devices close to one another and coupled by a telecommunication network in order to attenuate, in a signal picked up by at least one microphone of another of said at least two local communication device-devices including at least one microphone, the components of a signal broadcast by at least one loudspeaker of at least one communication device including at least one loudspeaker, the echo processing method comprising the steps of:

obtaining information representing the signal broadcast by [[the]]at least one loudspeaker of at least one communication device, and

transferring, by use of a dedicated coupling with at least one of the other devicelocal communication devices, the information obtained.

16. (Previously presented) Echo processing method according to claim 15, wherein the method also comprises obtaining information representing the coupling between at least one loudspeaker of the at least one communication device and the microphone of the other communication device.

Application No.: 10/560,523**Docket No.: 4976-008**

17. (Previously presented) Echo processing method according to claim 16, wherein the echo processing method also comprises weighting the information representing the broadcast signal of the communication device by coefficients associated with the information representing the couplings between at least one loudspeaker of said at least one communication device and the microphone of the other communication device.
18. (Previously presented) Echo processing method according to claim 16, wherein (a) the communication device comprises a plurality of loudspeakers, and (b) the signals reproduced by each loudspeaker of the said at least one communication device are weighted by respective coefficients representing the coupling between each loudspeaker of the communication device and the microphone of the other communication device, and (c) the weighted signals are added.
19. (Previously presented) Echo processing method according to claim 15, wherein the echo processing method also comprises determining the number of other communication devices and determining the number of loudspeakers of the other communication devices.
20. (Previously presented) Echo processing method according to claim 19, wherein the echo processing method also comprises:
- generating at least one predetermined audible signal,
- receiving, via coupling with at least one other device, information representing the reception of the audible signal by the at least one other device, and
- determining the coupling between the loudspeaker of the said communication device and the microphone of at least one other communication device.
21. (Previously presented) An information medium storing a computer program for

Application No.: 10/560,523Docket No.: 4976-008

causing a computer to perform the steps of claim 12.

22. (Previously presented) An information medium storing a computer program for causing a computer to perform the steps of claim 15.

23. (New) A system including a plurality of the devices of claim 1 wherein the dedicated coupling is arranged for coupling a wave including the information and an electric component, and the local communication devices are close enough to each other that acoustic waves are coupled between the microphones and loudspeakers of the local communication devices.

24. (New) A system including a plurality of the devices of claim 6 wherein the dedicated coupling is arranged for coupling a wave including the information and an electric component, and the local communication devices are close enough to each other that acoustic waves are coupled between the microphones and loudspeakers of the local communication devices.

25. (New) The method of claim 12 wherein the method is performed at each of the local communication devices, the dedicated coupling couples a wave including the information and an electric component, and the location communication devices are close enough to each other that acoustic waves are coupled between the microphones and loudspeakers of the location communication devices.

26. (New) The method of claim 15 wherein the method is performed at each of the local communication devices, the dedicated coupling couples a wave including the information and an electric component, and the location communication devices are close enough to each other that acoustic waves are coupled between the microphones and loudspeakers of the location communication devices.